



US005135599A

United States Patent [19]

Martin et al.

[11] Patent Number: **5,135,599**[45] Date of Patent: **Aug. 4, 1992**[54] **METHOD OF MAKING A TRIPLE LUMEN CATHETER**

[75] Inventors: Geoffrey S. Martin; Michael R. LeBlanc, both of Mississauga, Canada

[73] Assignee: Vas-Cath Incorporated, Mississauga, Canada

[21] Appl. No.: 699,421

[23] Filed: May 13, 1991

Related U.S. Application Data

[62] Division of Ser. No. 288,364, Dec. 22, 1988.

[30] **Foreign Application Priority Data**

Dec. 22, 1987 [CA] Canada 555076

[51] Int. Cl. B32B 31/00; A61M 3/00

[52] U.S. Cl. 156/294; 264/322; 604/43; 604/280

[58] Field of Search 604/39-46, 604/164-169, 264, 280, 283, 284; 264/322; 156/294, 60, 198, 293, 304.2, 304.5, 304.6, 308.2

[56] **References Cited****U.S. PATENT DOCUMENTS**

3,928,869	9/1970	Derenluk	156/294
3,634,924	1/1972	Blake et al.	29/447
4,072,146	2/1978	Howes	128/205
4,168,703	9/1979	Kenigsberg	604/280
4,251,305	2/1981	Becker et al.	604/103
4,390,383	6/1983	van Dongeren	156/294
4,406,656	4/1983	Hattler et al.	604/280


4,581,968	4/1986	Mahurkar	604/280
4,668,225	5/1987	Russo et al.	604/280
4,670,009	6/1987	Bullock	604/280
4,681,564	7/1987	Landreneau	604/280
4,769,005	9/1988	Ginsburg et al.	604/164
4,813,429	3/1989	Estel et al.	604/43
4,961,809	10/1990	Martin	603/280
4,968,307	11/1990	Dake et al.	604/280

Primary Examiner—C. Fred Rosenbaum
 Assistant Examiner—Mark W. Bockelman
 Attorney, Agent, or Firm—Rogers & Scott

[57] **ABSTRACT**

A method of manufacturing a multiple lumen catheter with a tapered tip and an end aperture concentric with the main catheter body is described. The method includes providing a flexible elongate body extending about a longitudinal axis having a distal end, a proximal end, an outer wall, a septum extending between spaced points on the outer wall to define first and second lumens, and a third lumen defined about said axis in a central portion of the septum. A straight wire is inserted into the third lumen to project centrally from the distal end of the body and the distal end of the body is then inserted into a tapering mould having a centrally located aperture to receive the wire. The distal end of the body is softened in the mould such that the distal end deforms to a tapered shape with the outer wall of the body merging with the septum to close the first and second lumens. Openings are then formed in the outer wall communicating with the first and second lumens adjacent the distal end.

3 Claims, 9 Drawing Sheets



Best Available Copy

Assignment Data Not Available

For Patent Number: 5135599

Search Results as of: 8/13/2004 1:55:12 P.M.

If you have any comments or questions concerning the data displayed, contact OPR / Assignments at 703-808-8723
Web interface last modified: Oct. 5, 2002

Best Available Copy